

Color-Kolmio Oy - Jatkuvan valon LED-tuotteet

Phottix®



Nuada Video LED Light



Nuada R3 II

81429 Nuada R3 II LED Light

P81428 Nuada R3 II Twin Kit

Power: 50W | CRI: ≥ 95

Battery: NP Series x 2 with adapter

Dimensions: 428 x 433 x 33mm

Weight: 1520g (not include battery)

Battery Life: 5600K at Max Power

NP-F550 XX min / NP-F750 XX min

NP-F970 XX min

P81429

319,00 verolla kpl

Phottix Nuada R3 II LED LIGHT TWIN KIT SET:



Color Rendering Index (CRI): - 95 Color Temperature (adjustable): 3200K~5600K Maximum Brightness: 1100Lux @ 1m Power: 40W Battery: V-mount / NP Series with adaptor Battery Life:5600K at Max Power 2 x NP-F550 (7.4V 2000mAh) 40min 2 x NP-F750 (7.4V 2000mAh) 95min 2 x NP-F970 (7.4V 2000mAh) 150min 1 x V Battery (14.4V 95Wh) 130min AC/DC adaptor: 100-240VAC Dimensions: 428 x 433 x 33mm Weight : 1520g Twin Pack Kit Dimensions: 800 x 410 x 160mm Twin Pack Kit Weight : 9580g

P81428

639,00 verolla kpl



Softlight Design for 70W of Flattering Light

Excellent Color - CRI Rating of 96+/TLCI 98+

Phottix LED Ecosystem (ECO1) via 2.4G Remote Control (range up to 164ft/50m) with 3 Groups and 40 Channels

Digital Brightness and Temperature Control

Powered by AC Adapter and V-mount Battery Operation (battery not included)

Compact Size – Only 12mm thick

Anti-Scratch Surface Panel

Carrying Bag

P81481

395,00 verolla kpl



Nuada S3

81421 Nuada S3 LED Light

Power: 35W | CRI: ≥ 95

Battery: Compatible NP Series x 2

Dimensions: 376 x 266 x 25mm

Weight: 1170g (not include battery)

Battery Life: 5600K at Max Power

NP-F550 45 min / NP-F750 110 min

NP-F970 175 min

P81421

159,00 verolla kpl

Nuada S

15W Suorakaide



P81420

129,00 verolla kpl



Nuada P

Pitkä suorakaide

P81420

129,00 verolla kpl

3300 to 5600K variable color temperature, CRI 95

LED screen and color temperature dial on back

Built-in L-series battery plate on back

Optional power with separately available 12 VDC power adapter

1/4"-20 mounting thread on bottom

Includes 2000mAh NP-F550 battery, USB battery charger, and shoe adapter



Nuada Ring 60

81461 Nuada Ring 60 LED Light

Power: 60W with USB 5V 2A output | CRI: ≥ 95

Battery: Compatible NP Series x 2

Dimensions: dia 487mm x 47mm

Weight: 1250g (not include battery)

Battery Life: 5600K at Max Power

NP-F550 25 min / NP-F750 75 min

NP-F970 120 min

P81461

195,00 verolla kpl



Nuada Ring 10 Go Kit

81470 Nuada Ring 10 Go Kits

Power: 10W | CRI: 96+

Input Power: USB 5V 2.1A input

Dimensions: dia 260mm x 10mm

Weight: 217g (without stand)

Included: MT-one Mini Tripod

P81470

69,00 verolla kpl



Phottix VLED Video LED Light 198A

81411 **59,00 verolla kpl**



Phottix VLED Video LED Light 198C

81412 **69,00 verolla kpl**

Stepless brightness adjustment
Lightweight, portable and compact
Adapters for popular camera batteries
White and orange diffusers included
Color temperature adjustable from 3200K to 7500K
Fits many DSLR cameras and camcorders



Phottix VLED Video LED Light 260A

81413 **85,00 verolla kpl**



Phottix VLED Video LED Light 260C

81414 **95,00 verolla kpl**

Stepless brightness adjustment
Lightweight, portable and compact
Adapters for popular camera batteries
White and orange diffusers included
Color temperature adjustable from 3200K to 7500K
Fits many DSLR cameras and camcorders

 **elinchrom**[®]

 **ELM8**



Elinchrom ELM8 on ammattitason LED-valo video -ja still-kuvaukseen. Valoteho on kunnioitettavat 8000 LM mikä mahdollistaa myös suurten valonmuokkaimien käytön. Valoteho ei riitä auringossa tapahtuvaan High Speed (HS) tyyliin kuvaukseen, mutta kaikkeen muuhun tällä saa laadukkaan ja ammattimaisen täytevalon.

LED-tekniikan ansiosta laite on langaton. Akkuista riittää virtaa täydellä teholla tunniksi tai osateholla useaksi tunniksi (245min). Akun latausaika on vain noin kaksi tuntia. Voit käyttää laitetta samaan aikaan kun se lataantuu mukana tulevalla AC-adapterilla. Laite on IP54-suojattu ja se kestää näin pölyä ja kosteutta.

Ominaisuuksia:

Erittäin laadukas valo: CRI - 93 / TLCI - 94

Väriämpötila - 5600 K (puhtaan valkoinen)

Kirkkaus: LUX - 16320 (at 1m w/Fresnel)

Valoteho: 8000 Lumenia

Valaisun kulma noin: 120°

Pöly- ja sääsuojaus: IP54

Impact Resistance: 1 m

Toimita-aika: jopa 245 min

Paino: 1.2 kg (2.645 lbs) (sis akun)

Latausaika: 2h (täysi lataus) Tällä välillä valaisinta voi käyttää myös verkkolaitteen kanssa samaan aikaan.

Koko: 20.5 x 9.6 x 9.6 cm (akun kanssa)

Etäohjaus: Elinchrom Skyport Protocol / Phottix Odin II

20 Frequencies / 4 Groups

Kantama: jopa 100 m

Takuu 24kk

ELM8 LED-valoon sopivat suoraan kaikki Elinchrom Quadran muotoiluosat. Jos haluat käyttää suurempia ns. perinteisiä Elinchrom studiosalaman osia tarvitset lisäksi osa: SOVITIN EL-BAJONETIN JA QUADRA-PÄÄN VÄLILLE (MK-II 26342)



**CONTINUOUS
LIGHT
SYSTEM
ELM8**



ELM8 (850-0390.EU)



EL Modifier
Interface
800-0343-A



50° Focus
Optic DM
800-0337-A



Fresnel 25°
800-0302-A



Glo Bulb
Diffuser
800-0282-A



Barn
Doors
800-0284-A



Speedring
Gel Holder
800-0283-B



Dome
Port DM
800-0335-A

SVH 1890,00 verolla

<https://www.elinchrom.com/continuous/elm8.html>

<https://www.youtube.com/watch?v=8XFQnQHxawU>

<https://www.youtube.com/watch?v=8iS1WyNZGsl>



Uudet tuotteet tulossa!

Tre-D 1000W DUAL COLOR

Mod. 515



Description

New led light "LIGHTLED 1000 DUAL COLOR" Mod. 515, with double color temperature from 3200°k to 6500°k, dimmable and also usable through a remote control FSK 2.4G (not included).

Cold light (6500°k), warm light (3200°k) or bicolor light (3200°k-6500°k).

High color rendering CRI and TLCI, with cooling fan, 100w only of power consumption and light output equivalent to 1000w tungsten.

It is including 5 kinds of scene light modes.

It is including 5 groups and 16 working channels.

Complete with diffusion and colored panels.

Complete with reflector.

Complete with super-fast swivel and 16mm socket for mounting on stands or whatever equipment.

Complete with umbrella attachment.

Specifications

- Alu housing.
- Light output equivalent to 1000w tungsten.
- Lumen: 10000
- Cri: >95
- Tlci: >95
- Dimmable.
- Adjustable color temperature.
- Cooling fan: included.
- Noise level: undetectable.
- Beam angle: 120°.
- Color temperature: 3200-6500°k (+/-200k).
- Voltage: DC24V-6A.
- Remote control distance: 80mt.
- Dimensions: cm. 24x10x11
- Weight: kg. 1,8



SVH 682,00 verolla

Tre-D 2000W DUAL COLOR

Mod. 516



Description

New led light "LIGHTLED 2000 DUAL COLOR" Mod. 516, with double color temperature from 3200°k to 6500°k, dimmable and also usable through a remote control FSK 2.4G (not included).

Cold light (6500°k), warm light (3200°k) or bicolor light (3200°k-6500°k).

High color rendering CRI and TLCI, with cooling fan, 200w only of power consumption and light output equivalent to 2000w tungsten.

It is including 5 groups and 16 working channels.

Complete with diffusion and colored panels.

Complete with reflector.

Complete with super-fast swivel and 16mm socket for mounting on stands or whatever equipment.

Complete with umbrella attachment.

Specifications

- Alu housing.
- Light output equivalent to 2000w tungsten.
- Lumen: 20000
- Cri: >95
- Tlci: >95
- Dimmable.
- Adjustable color temperature.
- Cooling fan: included.
- Noise level: undetectable.
- Beam angle: 120°.
- Color temperature: 3200-6500°k (+/-200k).
- Voltage: AC90V-240V / DC24V
- Remote control distance: 80mt.
- Dimensions: cm. 31x13x13
- Weight: kg. 2,8



SVH 998,00 verolla

STUDIOKING SPEEDRING ADAPTER BOWENS -> ELINCHROM

Tarvitaan Elincan valonmuokkaimille.

Toimitetaan Tre-D LED-valon mukana.



Lisälaitteet:

Tre-D REMOTE CONTROL 517 FOR LED LIGHT

SVH 79,00

Tre-D V LOCK ADAPTER 518 FOR LED LIGHT WITH CLAMP AND XLR

SVH 124,00

Yhteystiedot:

Color-Kolmio Oy

Tuotepäällikkö Kari Pälli

kari.paelli@colorkolmio.fi

040 718 4976

Color-Kolmio Ammattilaitteepiste Vantaa

<https://www.colorkolmio.fi/ammattilaiset/ammattilaitteet.html>



Color-Kolmio kotisivut

<https://www.colorkolmio.fi>

<https://www.colortukku.fi/fi/>